

Rubiomonocoat EXTERIOR WOOD CLEANER

DESCRIPTION:

Rubio Monocoat Exterior Wood Cleaner is a preparatory cleaner for all types of outdoor wood and composite materials. Removes grey discolouration, mildew stains and dirt.

DIRECTIONS FOR USE:

1. Dampen the surface with water. Use a garden hose or a high-pressure cleaner (caution: maximum of 40 bar).
2. Apply some **RMC Exterior Wood Cleaner**.
3. Scrub the treated area with a nylon scrubbing brush in the lengthwise direction of the wood until it is clean. This will cause the product to foam. For stubborn stains, repeat the treatment.
4. Rinse thoroughly until all the foam has disappeared.
5. Allow the surface to dry well (+/- 30 minutes at a temperature of 20 °C and proper ventilation).
6. Treat with the Rubio Monocoat exterior wood protection product of your choice.

A good preparation is crucial to ensure a lasting protective finish.

All new, greyed, and previously treated wood must always be treated beforehand with **RMC Exterior Wood Cleaner**.

BENEFITS:

- New wood:

- > grease that appears naturally in some types of wood is removed.
- > the pores are opened, this guarantees that the protective layer will last longer.

- Wood previously treated with another brand's product:

- > for saturation products applied to the wood longer than a year: **RMC Exterior Wood Cleaner** will remove all residues from previous treatments.
- > if a paint or varnish has been applied, the surface must be sanded, stripped or sand-blasted first.

USAGE:

Manual: +/- 15 m2/L

These usages are merely indicative. It is always recommended to make a sample in order to calculate the exact usage.

REFUSE:

Dispose of empty containers and waste in accordance with local regulations.

STORAGE:

The product can be stored for up to 12 months in a dry place and in the original packaging. Do not allow to freeze.

PACKAGING:

Bottle 100 ml and 1L, jerrycan 5L

YOUR DISTRIBUTOR:

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. Muylle Facon NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.



Consult the safety sheet before use.

Date TDS: 19/07/16

MUYLLE FACON

MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.
Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)
Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823
info@muyllefacon.be - www.rubiomonocoat.com

